



Head Office and Plant:  
Via Centallo, 57 - 10156 Turin  
Tel. +39-011 273.00.33  
Fax +39-011 273.56.17

s.r.l. [www.sivit.it](http://www.sivit.it)  
[ser.tec@sivit.it](mailto:ser.tec@sivit.it)

## Technical Sheet

Rev. B del 05/03 – Cod.1 -Sigla

### ALBI

#### Enamel of aluminium colour

##### Uses

- Metallic coverings
- Industrial window frame
- Top coating for bituminous waterproofing

##### Description

- Solvent- borne one-component product based on bitume, aluminium thin plate and thermoplastic resin. During the film formation the aluminium comes to the surface of the film forming a reflecting barrier that has protects the substrate from heat and UV-rays. Can be applied on difficult substrate, like bituminous protective covering and metallic material with excellent adhesion on rusty parts.

#### Preparation of the surface and application :

- ALBI can be applied without primer . Is sufficient to remove loose parts and apply the pure product by roller, brush or spray.
- Are adviced two hand.

#### TECHNICAL FEATURES:

COLOUR :	Silver
SOLID CONTENT:	54%
TACK FREE TIME :	25-35' ( 25°C - 50%U.R.)
CONSUMPTION:	1 lt for 4-6 mq
FLASH POINT:	34 ° C
APPLICATION CODITION:	Temperature between +5 °C and +35°C
HARDENING:	7 days (25°C - 50% U.R.)
SOLVENT TO CLEAN THE TOOLS:	Solvente UNI
STORAGE:	12 month. Keep in a dry place et a temperature between + 5° C and +35°C